



Department of Public Safety  
**WRECKER SERVICES DIVISION**  
**WRECKER INSPECTION REQUEST FORM**

FAX: (405) 425-2031  
 Email: wrecker@dps.ok.gov

Wrecker Service: \_\_\_\_\_ Class: \_\_\_\_\_ Date: \_\_\_\_\_

DPS#: \_\_\_\_\_ Contact: \_\_\_\_\_ Phone#: \_\_\_\_\_

**STOP: If you do not have DPS#, Call 405 425-2295 for instructions**

Office Address: \_\_\_\_\_ City/Zip: \_\_\_\_\_ County: \_\_\_\_\_

Storage Address: \_\_\_\_\_ Directions (on-site, etc.): \_\_\_\_\_

Inspection for: \_\_\_\_\_ Wrecker Vehicle:  Indoor Storage:  Outdoor Storage:   
 GVWR \_\_\_\_\_ Type: \_\_\_\_\_ Sling:  Rollback:   
*Must have current tag registered in wrecker service or wrecker owner's name* Wheelift:  Sling/Lift:

Tag#: \_\_\_\_\_ EXP: \_\_\_\_\_ VIN#: \_\_\_\_\_ Year: \_\_\_\_\_ Make: \_\_\_\_\_

**Business Sign:** Each AA Wrecker Service and each G Wrecker Service with storage shall have a business sign at the business location. The sign must be at least 2 feet by 4 feet with letters at least 3 inches high and shall display, at a minimum, the name of the business and a 24 hour a day telephone number.  Yes  No

**REQUIRED ON ALL VEHICLES REGARDLESS OF CLASS:**

- Pass standard vehicle inspection requirement
- DPS# and business name centered vertically at least 3" high
- One amber, rotating, flashing light with 360 degree visibility (perm. attached)
- 10# fire extinguisher or combination to 10#
- Warning devices (flares or triangles)
- Push-Type broom & shovel
- Tire chains or Mud & Snow tires
- Two chains to secure the load
- Two safety chains to keep the towed vehicle attached
- Tow lights (some rollbacks exempt only if capable of towing another vehicle)
- Safety Apparel - 1 high visibility vest, jacket or shirt per vehicle
- 4 Point tiedown (chains, cable or straps), if a rollback

**AA-SMALL TRUCK (not less than 9000# no max):**

- Axe
- Prybar
- Two Scotch" Blocks with Chains attached (rollback exempt)
- Sling" and "Stay-bar" or wheelift device, or rollback
- Dollies (TM, TL and rollback exempt),
- Dual rear wheels

(continued above right)

**AA-LARGE TRUCK (not less than 44,000#)**

(must have all AA-Small Truck and AA-Medium Truck Equipment plus:)

- Front axle & suspension (12,000#)
- Rear axle & suspension combination (32,000#)
- Full driven tandem axle
- Winch factory rated capacity of combined 40,000# equipped w/cable
- Minimum wheel base (280")
- 2 air hoses 3/8 in / 50 ft (considered as 2 or more air hoses 3/8" with combined minimum length of 100 ft)
- Cage Bolts (8)
- Two Air outlets on the wrecker for emergency and service line activation
- Metric and Standard end wrench sets with minimal 3/8 inch, 1/4 in, to 1 inch and 8mm to 19mm
- Metric and Standard 1/2 in drive socket set and ratchet with minimum 1/4 in to 1 in and 8mm to 19mm
- Hydraulic or Floor Jack with 10-ton minimum rating (hydraulic or pneumatic jack)
- 10 gallons of absorbent material
- 2.5 lb Sledge/shop hammer
- 2 pair locking pliers
- 4 axle covers
- 5 traffic cones (MUTCD compliant)
- Minimum of 4 (four) snatch blocks that are recommended for the size of rope contained on the winches
- Minimum of sixty feet (60") of one half inch (1/2") Grade 80 Recovery Chain with grab hooks
- 2 (two) - one inch (1") screw pin clevises
- 2 (two) - one half inch (1/2") screw pin clevises
- Boom(s) Wrecker unit must have a factory built or certified 25 (twenty-five) ton boom rating that is an elevation and telescoping recovery boom
- Wrecker unit must have a factory built or certified hydraulic telescoping wheel lift

The Department must have a current Certificate of Insurance on file covering this vehicle. The insurance verification form from the wrecker service will not be accepted, only our form will be accepted. Please contact your insurance company if they have not already sent in a Certificate of Insurance for the vehicle listed.